MAT JOURNALS
Journal of Controller and Converters
Volume 2 Issue 1

# Analysis of a Shrinking Span Membership function Method

***Prof. Rashmita Mehta, Prof. (Dr.) Srujal joshi , Smt. Sunita desai***
Department of Electrical & computer science Engineering
Government polytechnic, gandinagar, Email: sd551197@gmail.com

***Abstract***

*This paper indicates a Shrinking Span membership feature to be applied in very truth changing machine similar to VSC- HVDC system. on this particular work Mamdani controller as well as the Takagi-Sugeno controller are compared with genuine identical input feature(Shrinking Span membership) in simulation in addition to on prototype hardware. Simulation end result justify the. Takagi-Sugeno Controller gives higher dynamic reaction then the Mamdani controller.*

***Keywords:*** *Fuzzy Controller, Pulse width modulation, HVDC transmission.*

## INTRODUCTION

electricity electronics era improvement in conjunction with the particularly excessive switching frequency of Pulse Width Modulation, HVDC transmission gadget based upon VSC HVDC is implemented in some of unique events like connection of off-shore wind farms or oil drilling platforms to the mainland electrical community as well as for underground transmission or distribution system within crowded cities.

VSC HVDC device has a number of gain in evaluation with the conventional thyristor based HVDC, for example

- ✓ capability to connect to weak AC machine or even inactive structures,
- ✓ speedy reaction on account of stronger switching frequency (SPWM)
- ✓ minimum herbal surroundings effect
- ✓ No requirement of reactive energy with the aid of converter
- ✓ No upload-on to brief circuit ratio

then again, VSC HVDC transmission comes with quite some drawbacks, including probably big electrical power loss at the side of extensive funding value compared with traditional HVDC, but the technological innovation is continuously grow. VSC has got the capability to swiftly control both energetic and reactive strength independently of one another, to maintain the voltage and frequency regular. This provides standard flexibility close to the place of the converters within the AC device. The VSC format attracts on a modular strategy. For any highest DC voltages the device is set up in architectural systems. The favored sizes of the web site areas for that Converter stations are commonly compact. All equipment other than the strength transformer are interior. nicely-validated and examined equipment alongside on the manufacturing unit make installation and commissioning rapid and efficient. manage approach and control strategy have awesome effect at the characteristics of the VSC-HVDC gadget. A desirable control technique depends upon an accurate mathematic version. The VSC-HVDC working traits may be managed via a closed loop consists of control units and the manage device (PI controller)[1]. At present there's no direct analytic expression model offered of VSC-HVDC gadget.

There are definitely very few papers about quantitative optimization method of PI parameters. conventional technique utilized, to set PI parameters are as follows, Smith, Z-N and pole assignment

technique and so forth [2]. but for these types of approach switch feature is important, VSC-HVDC device is a double-enter and double-output nonlinear coupling item and its precise switch characteristic is hard to explain, so it is tough to make use of such traditional placing strategies to optimize PI parameters of VSC-HVDC manipulate machine. so that you can meet the dynamic universal performance requirement of the VSC-HVDC gadget, the paper [3] use estimation approach to set ok and Tn primarily based on PSCAD/EMTDC software program, however the estimation approach would not have theoretical basis and there's no

index chart to assess the manage gadget overall performance even as the use of envisioned parameters. In current years maximum of the papers have proposed methods for developing VSC controllers applying linear manage techniques, in which the gadget equations are line razed in a specific working point and based at the linearization model, PI or PD controllers are tuned at that point to be able to offer the first-rate feasible performance[7[-[8].

The drawback of such PI/PD controllers is that their parameters are usually tuned based on a mastering from their mistakes; additionally their performance degrades as the device operating circumstance trade. Nonlinear adaptive controller then again can offer appropriate control functionality over a extensive range of running circumstance; but they've a more state-of-the-art shape and extra difficult implementation in comparison to linear controllers.

This paper designs a traditional and changed Mamdani controller and Takagi-Sugeno controller for VSC HVDC gadget with shrinking span club characteristic. Simulation consequences are provided so that it will the performance of both the conventional (PI) and the modified controllers. The simulation consequences make sure that the control approach has speedy reaction, robust balance and reduction of losses.

This paper is organized as follow. In segment II, VSC HVDC device is defined, in section III the two kinds of fuzzy controller are defined with their comparison, in section IV represents the simulation outcomes, Conclusions are given in section V.

**VSC HVDC machine DESCRIPTION**

basic standards of VSC HVDC transmission operations can be demonstrate with the aid of taking into account each terminal as being a voltage supply coupled to the AC transmission network through a three segment reactor. Each terminals are interconnected with a DC hyperlink, as shown in fig 1.at the same time as in the document Station 1 is selected to manage reactive energy Q 1 and DC-bus voltage Udc, that's used as being a rectifier station, and Station 2 is scheduled to manage reactive power Q 2 and active energy P2, that is used being an inverter station .VSCHVDC converter is delivered in with pre and put up filters. The reason of pre filter is continually to normalizing the enter indicators according with the respective area, and the reason of submit filter out is usually to keep the output in the restrict price through saturation limiter, this block is simply now not shown within the schematic diagram however it is do not forget as inner block of converter.




***Fig 1*** *Schematic diagram of VSC HVDC device*

Fig 2 indicates a simplified single line diagram with the converter attached to AC gadget. The converter ismodeled as being a controlled voltage source uv at the AC aspect along with a controlled contemporary supply idc at the DC side.




***Fig 2.****unmarried line diagram of the converter connected to AC system*




***Fig3.*** *phasor diagram of vsc*

The energetic and reactive electricity are going to be recall as superb in case the power glide thru the AC network toward the converter. The segment displacement angle δ will likely then be positive while theconverter output voltage lags in the back of the AC voltage in phase.

**FUZZY CONTROLLERS**

Fuzzy logic structures offer a nonlinear mapping from the set of crisp enter to the set of crisp outputs, utilizingboth intuition and arithmetic. using distinct fuzzifiers as an instance Singleton, Gaussian and Triangular fuzzifiers, any set of crisp enter is mapped into a fuzzy set. Sever a regulations in rule base are positioned at the fuzzyinput a good way to produce a fuzzy output. This output finally defuzzified to create a crisp output fee sincerely, Defuzzification is a ultimate step in approximate reasoning additionally it contains inside the changing of a fuzzy set having a appropriate non-terrible actual number. Their are huge and sundry ways of Defuzzification for example

- ✓ center of location
- ✓ maximum middle of Gravity
- ✓ Centroid
- ✓ Fuzzy mean
- ✓ First of most
- ✓ ultimate of most
- ✓ middle of most
- ✓ exceptional approach
- ✓ Semi-linear Defuzzification
- ✓ Weighted Fuzzy imply

most center of Gravity and center of most are desired defuzzifiers put on to fuzzy good judgmentechniques.

Triangular fuzzifiers in addition to the centroid defuzzifier are being used in this

particular paper because the mappingstrategies.

two wonderful fuzzy logic techniques for developing controllers are Mamdani approach as well as the Takagi Sugenoechnique each of them are possessing these gain

**a) Mamdani technique**

- Is consumer-friendly
- Has wide-spread acknowledgement
- Is properly desirable to human enter

**b) Takagi-Sugeno method**

- Is computationally efficient
- Works successfully linear, adaptive andoptimization techniques
- Has assured a continual of theoutput floor
- appropriate for mathematical evaluation.

Takagi-Sugeno is a great deal higher with regard to dynamic device which in turn modifications right away in evaluationto Mamdani technique.

**A conventional Takagi-Sugeno Controller**

Fuzzy variables are ΔP, ΔQ, Δep, Δeq and fuzzy set with linguistic characteristics are bad very large,bad big, negative huge, bad small zero, nice small, high-quality huge, advantageous massive, high quality very bigare allocated to each variable and identical - span triangular characteristic have been chosen as being the fuzzy club feature as shown in fig 4.For Mamdani and Takagi-Sugeno input to controller is equal to defined above, but the subintervalsare heuristically decided on relying at the excellent damping performance. A identical sort of fuzzy rule base is beenassigned for each aggregate of enter/output variable to every types of controller like:

Rule1: IF (ΔP is NVB) AND (Δep is LNC) THEN (ΔM is BI)

Rule2: IF (ΔQ is NVB) AND (Δeq is LNC)
THEN (ΔΦ is BI)







***Fig 4(a)*** *Shrinking Span club feature* ***Fig 4(b)*** *identical Span Triangular features club function*

**SIMULATIOM**

so as to illustrate and compare the fuzzy techniques proposed, a simulation model is evolved using Simulink and the FIS toolbox of MatLab, for Mamdani controller as well as for Takagi-Sugeno controller. The SMPS fly returned with p.c 18F 4331 changed into used to design the fuzzy good judgment controller. It assist all deign step for fuzzy device engineering structure layout, linguistic variables and rule definition. This tool generates Ccode for Intel MCS-ninety six microcontrollers. It additionally produces M code which is used in MatLab. Mamdani controller as well as for Takagi-Sugeno controller. formulation are first created in C-code and then tested in MatLab. The gadget parameters are selected as according to the real current HVDC (traditional/classic) bipolar line between CHANDRAPUR and PADGHE.

**primary score**

The Chandrapur-Padghe HVDC bipolar is rated for 1500MW continuous energy go with the flow; a two-hour overload rating of 1650MW .The minimal energy go with the flow is scheduled at 65MW in monopolar functioning. The hyperlink isoperated at the direct voltage of ±400kV. at the AC aspect the hyperlink is hooked up to the 400kV device in both Chandrapur and Padghe. The AC voltage is allowed to very in among 380kV to 430kV in Chandrapur and in between 350kV to 320kV in Padghe. The frequency can fluctuate in between 48.5Hz and 50.5Hz.

There are four AC filter banks at each station. every financial institution is with a rating of 210MVAR. There are two DC filter branches consistent with pole and consistent with station as shown in fig 5.




**Easy VSC- HVDC 6-Pulse Transmission Device1500 MW (400kv) Chandrapur-Padghe**

**Step response**

in order to test the dynamic responses of the VSC HVDC machine, four check instances had been studied.

**Case 1 :** The simulation consists of electricity reversion from
-0.4 pu to +0. 4.5 pu of station 1 at t = 1.2s, then active strength step alternate from 0.5pu to at least one.opu at t = 1.5s,

**Case 2:** At t= 2.0s, the reactive strength step exchange from 0pu to -0.2pu of station 1, then set to +0.2pu at t = 2.5s

The machine hardware prototype implementation designed affords as 103.2 W and 110 VAR fig 6 present justone of the converter implemented due to the stations are same. This prototype system offers fast and realtime reaction.

Fig 7 gives the two strategies examined on the hardware system constructed with the same enter functions in all instances the proposed control Shrinking Span membership function with Takagi-Sugeno Controller gives improvement and really rapid response,.


***Fig 6*** *One converter of proto type VSC HVDC machine*




***Fig 7.****Dynamic reaction of the machine beneath two fuzzy controllers.*

## CONCLUSION

it's been proven in this application that a Shrinking Span membership feature gives higher and rapid reaction and Takagi-Sugeno Controller offers higher dynamic reaction. Shrinking Span membership function method is new venture and seeking out future trends for immediate performing device.

## REFERENCE

1. ChengyongGuangkai Li; Gengyin Li; Haifeng Liang; Ming Yin; Zhao; Operational Mechanism and function evaluation of Novel Hybrid HVDC system energy device era, 2006. power Con2006. international convention Oct. 2006 web page(s):1 – 6 virtual object Identifier 10.1109/ICPST.2006.321914
2. Chao; Zhou Xiaoxin; Li Ruomei; Dynamic Modeling and brief Simulation for VSC based HVDC in Multi- machine machine strength system technology, 2006. Power Con 2006.international convention on Oct. 2006 web page(s):1 - 7 digital item Identifier10.1109 / ICPST 2006.321603
3. Monsur,N.; Sood, V.k.; Lopes, L.; Modeling a Hybrid Diode-Thyristor HVDC Rectifier in EMTP-RV electrical and laptopEngineering, Canadian convention may 2006 web page(s):1258 - 1262 virtual item Identifier10.1109/CCECE.2006.277441
4. Latorre, H.F.; Ghandhari, M.; Soder, L.; manipulate of a VSC-HVDC operating in Parallel with ACTransmission strains L.;Transmission& Distribution conference and xposition: Latin the usa, 2006.TDC '06.IEEE/PES Aug. 2006 web page(s):1 - 5 virtualitem Identifier 10.1109 / TDCLA .2006.311394
5. Qahraman, B.; Gole, A.M.; Fernando,I.T.; Hybrid HVDC converters and their effect on electricity system dynamic overall perform an Engineering Society widespread assembly, 2006. IEEE 18-22 June 2006 page(s):6pp. virtual item Identifier10.1109/PES.2006.1708891
6. Bahrman, M.P.; evaluate OF HVDC TRANSMISSION strength systems convention and Exposition, 2006. p.c. '06. 2006IEEE PES Oct. 29 2006-Nov. 1 2006 page(s):18 – 23 digital item Identifier 10.1109 / p.c..2006.296221
7. Guangkai Li; Gengyin Li; Haifeng Liang; Chengyong Zhao; Ming Yin; studies on dynamic traits of VSC-HVDCmachine power Engineering Society preferred meeting, 2006. IEEE 18-22 June 2006 web page(s):five pp. virtual item Identifier10.1109/PES.2006.1709371
8. Tao Yu; Ka Wing Chan; Zhen Ren; Damping evaluation of primary and auxiliary manipulate of HVDC device energy EngineeringSociety fashionable assembly, 2006. IEEE 18-22 June 2006 page(s):6 pp. virtual object Identifier 10.1109/PES.2006.1709457
9. Saeedifard, M.; Nikkhajoei, H.; Iravani, R.; A area Vector Modulated Multi-Module Converter for again-to-back HVDCmachine strength Electronics experts conference, 2006. PESC '06. thirty seventh IEEE 18-22 June 2006 web page(s):1 – 6 digital itemIdentifier 10.1109 / PESC 2006.1711969
10. Wulue Pan; Yong Chang; Hairong Chen; Hybrid Multi-terminal HVDC machine for large Scale Wind power electricity systemsconvention and Exposition, 2006. p.c. '06. 2006 IEEE PES Oct. 29 2006-Nov. 1 2006 web page(s):755 - 759 digital object Identifier10.1109/percent.2006.296411